

ORIS Proof Color Tables - ISO Coated v2 - EPSON Stylus Pro 4880, 7880, 9880

Printing standard: ISO Coated v2 (FOGRA 39)
Printers: EPSON Stylus Pro 4880, 7880, 9880
Ink: Epson Ultrachrome K3, Photo Black
Resolution: Fein 720dpi
Printing mode: Bidirectional
Noise Filter: C=8%, M=8%, Y=8%, K=12%

Paper	Paper White Simul.	ORIS Color Table (DAT file)	Reference Printer Profile (RFP file)
ORIS Proof Premium 280 Semimatt White 280 g/m ²	Yes	108 Epson x880 Premium 280 ISOcoated v2.dat	108 Epson x880 Universal 280.rfp
	No	108 Epson x880 Premium 280 ISOcoated v2 Relativ.dat	108 Epson x880 Universal 280.rfp
ORIS PearlProof Super Semimatt White 200 g/m ² Semimatt White 240 g/m ² ORIS PearlProof Super V Semimatt White 235 g/m ²	Yes	104 Epson x880 Pearl Super ISOcoated v2.dat	104 Epson x880 Pearl Super.rfp
	No	104 Epson x880 Pearl Super ISOcoated v2 Relativ.dat	104 Epson x880 Pearl Super.rfp
ORIS PearlProof Select Semimatt 175 g/m ²	Yes	103 Epson x880 Pearl Select ISOcoated v2.dat	103 Epson x880 Pearl White - Pearl Select.rfp
	No	103 Epson x880 Pearl Select ISOcoated v2 Relativ.dat	103 Epson x880 Pearl White - Pearl Select.rfp
ORIS PearlProof White Semimatt White 185 g/m ²	Yes	103 Epson x880 Pearl White ISOcoated v2.dat	103 Epson x880 Pearl White - Pearl Select.rfp
	No	103 Epson x880 Pearl White ISOcoated v2 Relativ.dat	103 Epson x880 Pearl White - Pearl Select.rfp
ORIS Proof Satin Semimatt White 200 g/m ²	Yes	105 Epson x880 Satin ISOcoated v2.dat	105 Epson x880 Satin.rfp
	No	105 Epson x880 Satin ISOcoated v2 Relativ.dat	105 Epson x880 Satin.rfp

[English]

To achieve optimum color matches the printers have to linearized and calibrated using the RFP files listed here. Please refer to the *Color Tuner User Manual* for detailed instructions.

[Deutsch]

Für eine optimale Farbanpassung muss der Drucker linearisiert und mit den angegebenen RFP-Dateien kalibriert werden. Eine Anleitung finden Sie im *Color Tuner Benutzerhandbuch*.